



# CONNECTRIX MDS 9700 ENTERPRISE DIRECTORS

64Gb/s ready models

## Performance, scalability, high availability, analytics, automation and investment protection

The Connectrix™ MDS 9700 Directors have a fault-tolerant design and multiprotocol flexibility to support non-stop operations. The Connectrix MDS 9700 address the stringent requirements of large, virtualized data center storage environments. The MDS 9700 Directors provide high availability, scalability, security and ease of management with outstanding performance and powerful features for the all-flash, virtualized data center. All Connectrix MDS 16- and 32Gb/s platforms support FC-NVMe. Connectrix MDS Directors support the concurrent use of both traditional Fibre Channel and NVMe storage traffic, allowing organizations to seamlessly integrate Fibre Channel networks with next-generation NVMe-based storage, without a disruptive rip-and-replace.

### Connectrix MDS Director Chassis Models

There are five Connectrix MDS 9700 director models to address all your storage networking requirements. All chassis models include dual supervisor modules, fabric modules, fans and power supplies as noted in the specifications below. The models support 32- and 16Gb/s Fibre Channel line rate ports as well as NVMe, FCiP and FCoE protocols. The MDS-9710, MDS-9710-V2, MDS-9706 and MDS-9706-V2 also support mainframe FICON. The -V2 versions below are 64Gb/s ready.

- MDS-9718 – sixteen switching module slots, deliver up to 768 ports per chassis to enable consolidation at scale
- MDS-9710 and MDS-9710-V2 – with eight switching module slots each, these models support up to 364 ports per chassis
- MDS-9706 and MDS-9706-V2 – with four switching module slots, these directors provide up to 192 ports per chassis

### Connectrix MDS Optional Licensed Key Features

**Enterprise License** – includes advanced traffic engineering and network security features such as IVR, QoS, zoned-based QoS, Fibre Channel Security Protocol (FCSP), port security, VSAN-based access control and fabric binding.

**Mainframe Package** – includes features required for mainframe environments. FICON supports high-speed connectivity between mainframes and I/O devices. Features include VSAN for FICON and FCP intermixing, FICON Control Unit Port (CUP), Fabric Binding, Switch Cascading, FICON Native Mode Channel-to-Channel Operation, Persistent FICON FCID assignment, Port Swapping for host channel cable connectors, FICON Tape Acceleration.

**MDS SAN Analytics** – SAN Analytics is achieved through a built-in analytics engine on the 32Gb/s MDS switching module. The SAN Analytics engine is capable of producing I/O-level metrics so you can analyze in real time all Fibre Channel exchanges and report on metrics. The MDS Analytics solution is pervasive, there's no appliance, no probes and it's always on. There are two options for MDS SAN Analytics:

- SAN Insights License - enables access to telemetry data which Data Center Network Manager (DCNM) can display.
- SAN Telemetry Streaming License - provides the same data to 3<sup>rd</sup> party platforms like Virtual Instruments or for custom solutions.

### Connectrix MDS Management – Data Center Network Manager

Data Center Network Manager (DCNM) Server-based SAN License – includes advanced management capabilities such as vCenter integration, performance trending, advanced provisioning, backup and dashboards. License is hosted on a server.

Data Center Network Manager (DCNM) Switch-based SAN License – includes advanced management capabilities such as vCenter integration, performance trending, advanced provisioning, backup and dashboards. License is hosted on the switch.

There is also a free 30-day DCNM trial server-based license. You can download it at the following link:

<https://www.dell.com/support/home/en-us/product-support/product/connectrix-mds-series-software/drivers>

### **Intelligent Infrastructure Insights with Dell EMC CloudIQ**

CloudIQ combines machine intelligence and human intelligence to provide storage administrators with the intel they need to take quick action and more efficiently manage their Dell EMC environment. CloudIQ supports Dell EMC storage systems and Connectrix MDS.

## MDS 9700 Enterprise Directors

System Architecture	Technical Specification
Essential chassis components	<p>MDS-9718 - Base model includes six fabric modules, two supervisor modules, three fan trays and twelve power supplies. An additional four power supplies can be added to insure the highest level of power availability</p> <p>MDS-9710 and MDS-9710-V2 - Base model includes three fabric modules, two supervisor modules, three fan trays, and six power supplies. Additional two power supplies can be added to insure the highest level of power availability</p> <p>MDS-9706 and MDS-9706-V2 - Base model includes three fabric modules, two supervisor modules, three fan trays and four power supplies.</p>
Switching modules	<p>48-port 32 Gb/s module</p> <p>48-port 10GbE FCoE module</p> <p>24/10-port SAN Extension module with FCiP</p>
Cascade maximum	<p>MDS-9718 – 7</p> <p>MDS-9710 and MDS-9710-V2 - 5</p> <p>MDS-9706 and MDS-9706-V2 - 7</p>
Virtual SANs (VSANs)	Up to 80 VSANs per fabric
Performance	32Gb/s Fibre Channel full duplex, 10- and 40GigE
Switch core	Non-blocking, cross bar design
Buffer credits	<p>32Gb switching module - up to 500 per port (dedicated mode) standard and up to 8191 on individual port with Enterprise Package activated</p> <p>16Gb switching module - up to 500 per port (dedicated mode) standard and up to 4095 on individual port with Enterprise Package activated</p>
Maximum frame size	2112 bytes
Classes of service	Class 2, 3 and F
Fabric services	Simple Name Server, Registered State Change Notification (RSCN), Login Services, Fabric Configuration Service (FCS), Broadcast, In-order delivery
Fibre Channel port types	<p>Standard: E, F, FL and B</p> <p>Enhanced: SD, ST and TE</p>
Advanced functions	VSAN, IVR, PortChannel, QoS, N_Port ID Virtualization
Media types	<p>Hot swappable enhanced Small Form Factor Pluggable (SFP+) transceivers</p> <p>Short wave SFP+ up to 1,640 feet/500 meters</p> <p>Longwave SFP+ up to 6.21 miles 10 km</p>
Hot swappable components	Switching modules, SFPs, Supervisor modules, power supplies, fan assembly and Fabric modules
Installation options	19-inch Electronic industries Alliances (EIA) compliant rack or the Connectrix EC-1700 cabinet
Minimum NX-OS versions	<p>MDS-9718 – 7.3</p> <p>MDS-9710 – 6.2.1</p> <p>MDS-9710-V2 - 8.4(1)</p> <p>MDS-9706– 6.2.9</p> <p>MDS-9706-V2 8.4(1)</p>
Management	Data Center Network Manager (DCNM)
Management access	<p>MDS-9718 – Ethernet RJ-45; RS-232 Console CLI RJ-45</p> <p>MDS-9710 and MDS-9710-V2 – Ethernet RJ-45; RS-232 Console CLI RJ-45</p> <p>MDS-9706 and MDS-9706-V2 – Out-of-band 10/100/1000 Ethernet port, RS-232 serial console port</p>

Physical specifications	MDS-9718 Dimensions: (HxWxD) 45.25x17.3x35 inches (114.9x43.9x88.9 cm), 26RU Weight: 800 pounds fully loaded (363 kg)
	MDS-9710 and MDS-9710-V2 Dimensions: (HxWxD) 24.35x17.3x34 inches (61.9x43.9x86.4 cm), 14RU Weight: 450 pounds fully loaded (204 kg)
	MDS-9706 and MDS-9706-V2 Dimensions: (HxWxD) 15.6 x17.3x32 inches (39.62x43.9x81.3 cm), 9RU Weight: 325 pounds fully loaded (147.42 kg)
Interoperability	Refer to the Dell EMC Support Matrix (ESM), E-Lab Navigator or E-Lab Navigator mobile app

## MDS-9700 Enterprise Directors

Power and airflow	Technical Specification
Power supply	3000W AC
Input voltage	100 to 240v AC nominal (+/- 10% full range); 50 to 60 Hz nominal (+/-3 Hz for full range)
Output voltage	1452W 50V +/-4%/28A, 3.4 V +/-4%/15A (100 to 120V AC input). 3051W 50V +/- 4%/60A and 3.4 +/- 4%/15A (200 to 240V AC input)
Airflow	<p>MDS-9718 - provides 30 to 100 cubic feet per minute (CFM) total flow through each line card slot depending on the line card type and the fan speed setting. With the MDS-9718, the original manufacturer recommends that you maintain a minimum air space of 7 inches (17.78 cm) between walls, such as in a cabinet, on the side and on the top and bottom of the chassis. The chassis front air vents need a clearance of 12 inches, and the back-air vents need a clearance of 36 inches from a solid obstruction such as a solid wall.</p> <p>MDS-9710, MDS-9710-V2 – front to back</p> <p>MDS-9706, MDS-9706-V2 – front to back</p>

## MDS-9700 Enterprise Directors

Environmental specifications	Technical Specification
Temperature ambient operating	32 to 104 degrees F (0 to 40C)
Temperature ambient non-operating	-40 to 158 degrees F (-40 to 70C)
Relative humidity, ambient (non-condensing) operating	10 to 90%
Altitude operating	-197 to 6500 feet (-60 to 2000 m)

## MDS-9700 Enterprise Directors

### Regulatory compliance

### Technical Specification

Safety

- CE Marker
- UL 60950
- CAN/CSH – C22.2 No. 60950
- EN 60950
- AS/NZS 3260
- IEC 60825
- EN 60825
- 21CFR 1040

EMC

- FCC Part 15 (CFR 47) Class A
- ICES-003 Class A
- EN 55022 Class A
- CISPR 22 Class A
- AS/NZS 3548 Class A
- EN 55024
- EN 50082-1
- EN 61000-6-1
- EN 61000-3-2
- EN 61000-3-3

FIPS

- FIPS Certified
- FIPS 140-2 Level 2

## MDS-9700 Enterprise Directors

### Network security

### Technical Specification

- Per VSAN RBAC using RAIDUS and TACACS+-based authentication, authorization and accounting (AAA) functions
- VSAN Fabric Isolation
- Intelligent packet inspection at port level
- Fibre Channel Security Protocol (FC-SP) from host-to-switch and switch-to-switch authentication
- Secure File Transfer Protocol (SFTP)
- Secure Shell Version 2 (SSHv2) with Advanced Encryption Services (AES)
- Simple Network Management Protocol version 3 (SNMPv3) with Advanced Encryption Services (AES)
- Other built-in security: Control plane security, logical unit number (LUN) zoning and read-only zones, hardware enforced zoning and broadcast zones, management access FIPS 140-2 compliance. Other enhanced security features are available in the Enterprise Package.

## MDS-9700 Enterprise Directors

### Availability

### Technical Specification

Redundant, hot-swappable supervisor modules  
Redundant, hot-swappable fabric modules  
Hot swappable switching modules and hot swappable SFP+ optics

Redundant AC Input  
Redundant, hot-swappable power supplies and fans

Online, non-disruptive software upgrades and activation  
Non-disruptive subsystem maintenance

Stateful supervisor module failover

Stateful process restart  
E-mail home capability with DCNM 7.2.3+  
Fabric-based multipathing  
Per-VSAN fabric services  
Online diagnostics  
Port tracking  
Virtual Routing Redundancy Protocol (VRRP)



## Dell Technologies Services

Plan, deploy, manage and support  
IT transformation with our top-rated  
services

### **Consulting**

Dell Technologies Consulting Services provides industry professionals with a wide range of tools and the experience you need to design and execute plans to transform your business.

### **Deployment**

Accelerate technology adoption with ProDeploy Enterprise Suite. Trust our experts to lead deployments through planning, configuration and complex integrations.

### **Management**

Regain control of operations with flexible IT management options. Our Residency Services help you adopt and optimize new technologies and our Managed Services allow you to outsource portions of your environment to us.


### **Support**

Increase productivity and reduce downtime with ProSupport Enterprise Suite. Expert support backed by proactive and predictive artificial intelligence tools.

### **Education**

Dell Technologies Education Services help you develop the IT skills required to lead and execute transformational strategies. Get certified today.

Learn more at [DellTechnologies.com/Services](https://DellTechnologies.com/Services)



[Learn More](#) about  
Connectrix solutions



[Contact](#) a Dell Technologies Expert