




# ECS EX-Series

Dell EMC ECS is a software-defined, cloud-scale, object storage platform.

With ECS, any organization can deliver scalable public cloud services with the reliability and control of a private-cloud infrastructure. ECS provides comprehensive protocol support for unstructured—object and file—workloads on a single modern storage platform. Using ECS, organizations can easily manage globally distributed storage infrastructure under a single global namespace with anywhere access to content. ECS features a flexible software-defined architecture that is layered to promote limitless scalability. Each layer is completely abstracted and independently scalable with high availability and no single points of failure. ECS also comes in a fully-integrated turnkey appliance that bundles software and Dell PowerEdge servers into an easily deployed object system.

ECS is currently in its third generation of hardware appliances, the EX-Series, building on the legacy of Dell EMC’s Centera and Atmos object storage platforms which predated ECS. The ECS EX-Series is comprised of three unique hardware products: the EX300, EX500 and EX3000.

| ECS EX300  | ECS EX500   | ECS EX3000  |
|--|---|---|
|    |    |   |
| <p>As a starter edition, the EX300 lowers object storage adoption entry barriers with 60TB starting cluster options.</p> <p>With the capacity to grow to exabyte-scale, this is the ideal sandbox for in-house, cloud-native, mobile and web application storage. It’s also the optimal system to modernize existing Centera or Atmos deployments.</p> | <p>The perfect blend of economy and density, the EX500 injects even greater flexibility into the ECS appliance portfolio.</p> <p>With rack capacity ranging from 480TB to 4.6PB, the EX500 is a versatile option for midsized enterprises looking to support either modern application or deep archive use cases.</p> | <p>A high density, hot disk-swappable, object storage system, the EX3000 packs up to 8.6PB per rack and can grow into exabyte-scale with ease.</p> <p>It’s an ideal platform for long-term retention, storage consolidation and multi-purpose object storage requirements that span S3, HDFS and archive workloads.</p> |

## ECS EX-Series appliance overview

| Features                    | EX300  | EX500  | EX3000S / EX3000D   |
|-----------------------------|--|--|---|
| <b>Node architecture</b>    | <ul style="list-style-type: none"> <li>Intel x86 servers</li> <li>Integrated storage</li> <li>12 disk drives per node</li> </ul> | <ul style="list-style-type: none"> <li>Intel x86 servers</li> <li>Integrated storage</li> <li>12 or 24 disk drives per node</li> </ul> | <ul style="list-style-type: none"> <li>Intel x86 servers</li> <li>Integrated storage</li> <li>EX3000S: Up to 90 disk drives per node</li> <li>EX3000D: Up to 45 disk drives per node</li> </ul> |
| <b>Network connectivity</b> | <ul style="list-style-type: none"> <li>10GbE FrontEnd</li> <li>10GbE BackEnd</li> </ul>  | <ul style="list-style-type: none"> <li>25GbE FrontEnd</li> <li>25GbE BackEnd</li> </ul>  | <ul style="list-style-type: none"> <li>25GbE FrontEnd</li> <li>25GbE BackEnd</li> </ul>   |

|  |   |   |  |
|--|---|---|--|
| <b>40U rack configurations</b>         | <ul style="list-style-type: none"> <li>1, through 16 node configurations (5 node minimum initial rack)</li> <li>HA power</li> </ul> | <ul style="list-style-type: none"> <li>1, through 16 node configurations (5 node minimum initial rack)</li> <li>HA power</li> </ul> | <ul style="list-style-type: none"> <li>EX3000S: 1, through 8 node configurations (5 node minimum initial rack)</li> <li>EX3000D: 2, 4, 6, 8, 10, 12, 14 and 16 nodes (6 node minimum initial rack) configurations</li> <li>HA power</li> </ul> |
| <b>Multiple storage configurations</b> | <ul style="list-style-type: none"> <li>Unstructured storage up to 1536TB per rack</li> </ul>  | <ul style="list-style-type: none"> <li>Unstructured storage up to 4608TB per rack</li> </ul>  | <ul style="list-style-type: none"> <li>Unstructured storage up to 8640TB per rack</li> </ul>   |

### ECS EX-Series appliance details

| Features                            | EX300   | EX500   | EX3000S / EX3000D  |
|-------------------------------------|---|---|--|
| <b>Architecture</b>                 | <ul style="list-style-type: none"> <li>Standard 40U cabinet</li> <li>2U node containing server and disks</li> <li>Fully accessible – field serviceable</li> <li>Conventional front to back cooling</li> <li>HA power cabling and cooling</li> </ul> | <ul style="list-style-type: none"> <li>Standard 40U cabinet</li> <li>2U node containing server and disks</li> <li>Fully accessible – field serviceable</li> <li>Conventional front to back cooling</li> <li>HA power cabling and cooling</li> </ul> | <ul style="list-style-type: none"> <li>40U extra deep cabinet</li> <li>EX3000S: 4U chassis containing one server and disks</li> <li>EX3000D: 4U chassis containing two servers and disks</li> <li>Fully accessible – field serviceable components</li> <li>Conventional front to back cooling</li> <li>HA power cabling and cooling</li> </ul> |
| <b>Min / max cluster size</b>       | <ul style="list-style-type: none"> <li>5 node minimum</li> <li>No maximum</li> </ul>  | <ul style="list-style-type: none"> <li>5 node minimum</li> <li>No maximum</li> </ul>  | <ul style="list-style-type: none"> <li>Single: 5 node minimum</li> <li>No maximum</li> </ul>   |
| <b>Min / max rack configuration</b> | <ul style="list-style-type: none"> <li>Min: 1 node = 1 server with included disks</li> <li>Max: 16 nodes = 16 servers with included disks</li> </ul>  | <ul style="list-style-type: none"> <li>Min: 1 node = 1 server with included disks</li> <li>Max: 16 nodes = 16 servers with included disks</li> </ul>  | <ul style="list-style-type: none"> <li>Single: <ul style="list-style-type: none"> <li>Min: 1 chassis = 1 server + disks</li> <li>Max: 8 chassis = 8 servers + disks</li> </ul> </li> <li>Dual: <ul style="list-style-type: none"> <li>Min: 1 chassis = 2 servers + disks</li> <li>Max: 8 chassis = 16 servers + disks</li> </ul> </li> </ul>   |
| <b>Node:disk ratios</b>             | <ul style="list-style-type: none"> <li>1:12</li> </ul>  | <ul style="list-style-type: none"> <li>1:12, 1:24</li> </ul>  | <ul style="list-style-type: none"> <li>EX3000S: 1:45, 1:60, 1:90</li> <li>EX3000D: 1:30, 1:45</li> </ul>   |
| <b>Disk type (7200rpm, SATA)</b>    | <ul style="list-style-type: none"> <li>1TB, 2TB, 4TB, 8TB</li> </ul>  | <ul style="list-style-type: none"> <li>8TB, 12TB</li> </ul>   | <ul style="list-style-type: none"> <li>12TB</li> </ul>   |
| <b>Raw capacity (per node)</b>      | <ul style="list-style-type: none"> <li>12TB, 24TB, 48TB, 96TB</li> </ul>  | <ul style="list-style-type: none"> <li>96TB, 192TB, 144TB, 288TB</li> </ul>   | <ul style="list-style-type: none"> <li>540TB, 720TB, 1080TB / 360TB, 540TB</li> </ul>  |

|                                      |   |   |   |
|--------------------------------------|---|---|---|
| <b>Max raw capacity (per rack)</b>   | <ul style="list-style-type: none"> <li>192TB, 384TB, 768TB, 1536TB</li> </ul>   | <ul style="list-style-type: none"> <li>3072TB, 4608TB</li> </ul>  | <ul style="list-style-type: none"> <li>8640TB</li> </ul>  |
| <b>Node dimensions</b>               | <ul style="list-style-type: none"> <li>2U x D (715.5 mm)</li> <li>Weight: 33KG (with 12 drives)</li> </ul>  | <ul style="list-style-type: none"> <li>2U x D (810 mm)</li> <li>Weight: 43.2KG (with 24 drives)</li> </ul>  | <ul style="list-style-type: none"> <li>4U x D (1098.4 mm)</li> <li>Weight: 134 KG (with 90 drives)</li> </ul>   |
| <b>Rack dimensions</b>               | <ul style="list-style-type: none"> <li>H(75") x W(24") x D(47") + 4" for front door H(1905mm) x W(610mm) x D(1194mm)</li> <li>Weight: 887kg/1955lb with 4 switches, 16 2U nodes</li> </ul>  | <ul style="list-style-type: none"> <li>H(75") x W(24") x D(47") + 4" for front door H(1905mm) x W(610mm) x D(1194mm)</li> <li>Weight: 887kg/1955lb with 4 switches, 16 2U nodes</li> </ul>  | <ul style="list-style-type: none"> <li>H(75") x W(24") x D(53") + 4" for front door H(1903mm) x W(607mm) x D(1334mm)</li> <li>Weight: 1352kg/2980lb with 4 switches, 8 4U chassis</li> </ul>  |
| <b>Max power</b>                     | <ul style="list-style-type: none"> <li>0.29 kVA per 2U node</li> </ul>  | <ul style="list-style-type: none"> <li>.72 kVA per 2U node</li> </ul>   | <ul style="list-style-type: none"> <li>1.35 kVA per 4U chassis</li> </ul>   |
| <b>Max heatload</b>                  | <ul style="list-style-type: none"> <li>800 Btu/Hr for every 2U node</li> </ul>  | <ul style="list-style-type: none"> <li>2400 Btu/Hr for every 2U node</li> </ul>   | <ul style="list-style-type: none"> <li>4500 Btu/Hr for every 4U chassis</li> </ul>  |
| <b>Power specifications (server)</b> | <ul style="list-style-type: none"> <li>2X750W power supplies per node (HA)</li> </ul>   | <ul style="list-style-type: none"> <li>2X1100W power supplies per node (HA)</li> </ul>  | <ul style="list-style-type: none"> <li>2X1100W (EX3000S) power supplies per node (HA)</li> <li>2x1600W (EX3000D)</li> </ul>   |
| <b>Power specifications (rack)</b>   | <ul style="list-style-type: none"> <li>Connection: 4 single phase L6-30 (redundant power) <ul style="list-style-type: none"> <li>32A circuit breaker (A) max. per AC power source</li> </ul> </li> <li>2 three-phase WYE S52.30 (redundant power) <ul style="list-style-type: none"> <li>32A circuit breaker (A) max. per AC power source</li> </ul> </li> <li>2 three-phase delta CS-8365C (redundant power) <ul style="list-style-type: none"> <li>50A circuit breaker (A) max. per AC power source</li> </ul> </li> <li>Input voltage (VAC): 200-240</li> <li>Frequency (Hz): 50 - 60</li> </ul> | <ul style="list-style-type: none"> <li>Connection: 4 single phase L6-30 (redundant power) <ul style="list-style-type: none"> <li>32A circuit breaker (A) max. per AC power source</li> </ul> </li> <li>2 three-phase WYE S52.30 (redundant power) <ul style="list-style-type: none"> <li>32A circuit breaker (A) max. per AC power source</li> </ul> </li> <li>2 three-phase delta CS-8365C (redundant power) <ul style="list-style-type: none"> <li>50A circuit breaker (A) max. per AC power source</li> </ul> </li> <li>Input voltage (VAC): 200 240</li> <li>Frequency (Hz): 50 - 60</li> </ul> | <ul style="list-style-type: none"> <li>Connection: 6 single phase L6-30 (redundant power) <ul style="list-style-type: none"> <li>32A circuit breaker (A) max. per AC power source</li> </ul> </li> <li>2 three-phase WYE S52.30 (redundant power) <ul style="list-style-type: none"> <li>32A circuit breaker (A) max. per AC power source</li> </ul> </li> <li>2 three-phase delta CS-8365C (redundant power) <ul style="list-style-type: none"> <li>50A circuit breaker (A) max. per AC power source</li> </ul> </li> <li>Input voltage (VAC): 200-240</li> <li>Frequency (Hz): 50 - 60</li> </ul> |
| <b>Connectivity</b>                  | <ul style="list-style-type: none"> <li>Uplink connectivity: up to 16x10 GbE, 16x25 GbE or 8x100GbE uplinks to customer network (800 Gb/s maximum bandwidth), including high availability configuration</li> <li>Network: dual 25 GbE front end switches and dual 25 GbE back end switches (internal traffic) per rack</li> </ul>  |   |   |
| <b>Environmental specifications</b>  | <ul style="list-style-type: none"> <li>Operating temperature (°F/°C): 41 - 90/ 5 - 32</li> <li>Max. altitude: 7,500 ft/ 2,286 m @ 90°F/32°C</li> <li>Relative humidity: 20 - 80% non-condensing</li> <li>Raised floor: not required</li> </ul>  |   |   |
| <b>Options</b>                       | <ul style="list-style-type: none"> <li>Scale out by additional nodes only</li> </ul>  | <ul style="list-style-type: none"> <li>Scale out by additional nodes</li> <li>12 drive capacity upgrade kit</li> </ul>  | <ul style="list-style-type: none"> <li>Scale out by additional nodes</li> <li>15 drive node upgrade kit</li> </ul>  |



Learn more about Dell EMC ECS solutions



Connect with a Dell EMC Expert



Join the conversation with #DellEMCStorage